

CT-HDVD-EXT-IR394 Transmit HD Signals, Infrared Control & RS232 Over a Single Cat5e / 6

...competitive technologies with compelling value

Features:

- Distributes HDMI, bi-directional infrared control and RS-232 over a single Cat5e or Cat6 4 Pair cable
- Extends transmission distance up to 20 Meters / 394' from sources up to 1080p using Cat6 cable (100M / 328' Cat5e, 80M / 262' Cat5)
- Features advanced HDbitT over IP technology
- Supports resolutions up to 1920 x 1080@60Hz.
- Supports 20 60KHz IR
- Bi-directional RS232
- Receive unit can be powered over the twisted pair cable by the transmitter
- · Plug and play, no settings or adjustments required
- · Durable metal housing



Description:

The CableTronix CT-HDVD-EXT-IR394 HDMI extender applies advanced HDbitT over IP technology to transmit 1080p HDMI signals over a single Cat5/5e/6 cable up to 394 feet (120 meters). It supports IR pass-back and bi-directional RS232 to control the HDMI source device from the remote unit. The receiver can be powered by the transmitter over the twisted pair cable.

The CT-HDVD-EXT-IR394 uses HDbitT technology to transport HDMI signals over long distances beyond the capability of HDMI cables alone. With easy to read LED indicators to confirm link status and the ability to use an existing ethernet cable to add in IR control this system can be a significant time saver in both the residential and commercial markets.

Specifications:

HDMI signal HDMI 1.3, compatible with HDCP 1.2

Transport Protocol HDbitT

Resolution Supported 480i@60Hz, 480p@60Hz, 576i@50Hz,

720p@50/60Hz, 1080i@50/60Hz,

1080p@50/60Hz

Network cable UTP/STP CAT5, CAT5e, CAT6

Transmission length Cat6: 120 Meters, 394 Feet

Cat5e: 100 Meters, 328 Feet

Cat5e: 100 Meters, 328 Feet Cat5: 80 Meters, 262 Feet

Infrared back 20 - 60kHz Bi-directional IR transmission

RS232 Bi-directional

Working Temperature 0°C - 60°C (32°F - 140°F)

Power supply One DC12V/3A

Power consumption 8W

Transmitter dimensions 4.11"L x 3.8"W x 0.94"H
Receiver dimensions 4.11"L x 3.8"W x 0.94"H
Enclosure material Black Metal Housing

Transmitter weight 0.51 lbs. Receiver weight 0.53 lbs.

CT-HDVD-EXT-IR394 Contents Include:

1 HDMI Extender transmitter

1 HDMI Extender receiver

1 Power supply

l IR Target

1 IR Emitter

2 RS232 Serial port caps1 Operating Instructions

CT-HDVD-EXT-IR394RX Contents Include:

1 HDMI Extender receiver

1 Power supply

1 IR Target

RS232 Serial port caps

1 Operating Instructions

Email: sales@cabletronix.com Web: www.cabletronix.com