

CT-HDVD-MINI1X2SPL-V2

HDMI 1 × 2 Splitter

This HDMI Splitter can distribute 1 HDMI input signal source to 2 HDMI displays simultaneously. Supported video resolution is up to 4K×2K@30Hz. It supports digital audio formats: DTS-HD/Dolby true-HD/LPCM 7.1/DTS/Dolby-AC3/DSD. The product supports HDMI signal input debounce and output amplification functions, and is perfectly compatible with all current HDMI source devices and display devices.



Key Features

- HDMI 1.4b and HDCP 1.4 compliant
- Supports video resolution up to 4K×2K@30Hz
- Supports 3D video format
- Supported color depths: 30-bit, 36-bit and 48-bit/pixel
- Supported audio formats: DTS-HD/Dolby-true-HD/LPCM 7.1/DTS/Dolby-AC3/DSD
- Compact design for easy and flexible installation

Technical

HDMI Compliance	HDMI1.4b
HDCP Compliance	HDCP1.4
Video Bandwidth	2.97Gbps
Video Resolution	Up to 4K×2K@30Hz
Audio Formats	DTS-HD/Dolby-true-HD/LPCM 7.1/DTS/Dolby- AC3/DSD
Color Depth	30bit, 36bit and 48bit/pixel
ESD Protection	Human body model: ± 8 kV (air-gap discharge) ± 4 kV (contact discharge)

Connection

Input Ports	1 x HDMI Type A (19-pin female)
Output Ports	2 x HDMI Type A (19-pin female)

Mechanical

Housing	Metal Enclosure
Silkscreen Color	Black
Dimensions	2.36" x 2.75" x 0.787" (60 x 70 x 20mm)
Weight	0.27 lbs (125 g)
Power Supply	DC 5V/1A
Power Consumption	1.5W
Operation Temperature	32 - 104°F (0 - 40°C)
Storage Temperature	-4°F - 140°F (-20 - 60°C)
Relative Humidity	20 - 90% RH (non-condensing)
Warranty	1 year - Can be extended to 3 years