

## CT-HDEXT-295-4K

## HDMI Extender over CAT6 – 4K UHD up to 295 ft

Extend your HDMI signal up to 295 feet (90 meters) at 4K@60Hz or 394 feet (120 meters) at 1080p@60Hz using standard CAT6/6A/7 network cable. The CT-HDEXT-295-4K includes a transmitter and receiver pair and supports HDR10, Dolby Atmos, EDID passthrough, and auto downscaling. It features IR control, ARC support, and digital audio out (S/PDIF). Perfect for digital signage, home theater, and conference room AV distribution.

## **Key Features**

- Ultra HD 4K Support -Resolutions up to 4096 x 2160 @60Hz
- IR Control IR target allows signal to pass from HDMI receiver at the TV, back to the HDMI transmitter and control the source via IR blaster
- Compact & Durable Design: Metal housing with compact footprint
- Dimensions: 4.15" x 4.03" x 0.79"
- Each unit weighs approx. 0.53 lbs
- Includes mounting brackets and screws
- Plug-and-play with LED indicators and reset buttons
- Powered by DC5V/1A adapters (included)



	Specifications	
Power Supply	Voltage/Current	DC5V/1A
	Power Consumption	TX <4W RX <4W
HDMI Performance & Interface	HDMI Compliance	HDMI 2.0
	HDCP Compliance	HDCP 2.2
	HDMI Resolution	MPEG2
	Supports Audio Formats	LPCM/DTS-H D/DTS-Audi/ Dolby Digital 5.1CH/Dolby Atmos
	Input & Output TMDS Signal	0.7-1.2Vp-p (TMDS)
	Input & Output DDC Signal	5Vp-p(TTL)
	Input Cable Length	≤8m (AWG24)
	Output Cable Legth	≤8m (AWG24)
Transmission Distance	CAT6/6A/7	14K@60Hz transmission 90m 1080p@60Hz transmission 120m
Protection Level	Electrostatic Protection of the Whole Machine	1a Contact discharge level 3 1b Air discharge Level 3 Implementation of the standard: IEC61000-4-2
Operating Enviroment	Working Temperature	-4 - 140°F (-20 - 60°C)
	Storage Temperature	-22- 158°F (-30 - 70°C)
	Humidity ( No condensation)	0-90% RH
General	Dimensions	4.15 x 4.03 x 0.79" (105.5 x 102.5 x 20mm)
	Weights	TX: 0.53 lbs. ( 243g) Rx: 0.53 lbs. ( 243g)
	Material	Iron
	Color	Black
	Warranty	2 Years Limited Warranty