

100Mbps Unmanaged Power over Ethernet (PoE) Switches


Features:

- IEEE 802.3at and IEEE 802.3af Power over Ethernet (PoE) compliant
- Up to 30 watts per PoE port
- 4 kV surge protection for PoE ports
- IEEE 802.3x flow control support
- Plug-and-play installation
- Sturdy metal enclosure
- 1 Year warranty



Ordering Information:

IP-POE4	4 Port PoE Switch
IP-POE8	8 Port PoE Switch
IP-POE16	16 Port PoE Switch
IP-POE24	24 Port PoE Switch



Specifications

	IP-POE4	IP-POE8	IP-POE16	IP-POE24
Ports				
Network Ports	5	9	18	26
PoE Port	4, 10/100Mbps RJ45 ports	8, 10/100Mbps RJ45 ports	16, 10/100Mbps RJ45 ports	24, 10/100Mbps RJ45 ports
Uplink Port	1, 100M Ethernet Port	1, 100M Ethernet Port	2, 1000M Combo Port	2, 1000M Combo Port
Standard	IEEE802.3,802.3u,802.3x, 802.3af, 802.3at			
Performance				
Switching Capacity	1Gbps	1.8Gbps	7.2Gbps	8.8Gbps
Max. Forwarding Rate	0.74Mpps	1.34Mpps	5.36Mpps	6.55Mpps
High Priority Ports	Port 1	Ports 1-2	Ports 1-8	Ports 1-8
Forwarding Mode	Store-and-forward			
MAC Address Table	1k	4k	4k	4k
Flow Control	IEEE802.3x full duplex			
Power Over Ethernet				
PoE Standard	IEEE802.3af, IEEE802.3at			
PoE Power Budget	58W	123W	230W	370W
Working Mode	Extend On:250m,10M,CAT 5e, Extend Off:100m			
General				
Power Supply	51V DC, 1.25A	51V DC, 2.5A	100-240V AC, 50/60Hz	100-240V AC, 50/60Hz
Power Consumption	<63W	<127W	<250W	<440W
Surge Protection	4KV			
Working Temperature	Temperature: 0°C - 40°C, 32°F - 104°F			
Working Humidity	Humidity: 10%-90% , non-condensing			
Storage Temperature	Temperature: -40°C - 70°C, -40°F - 158°F			
Storage Humidity	Humidity: 5%-90% , non-condensing			
Weight	0.299kg, 0.66 lbs.	0.57kg, 1.26 lbs.	3.72kg, 8.2 lbs.	4.29kg, 9.46 lbs.
Dimensions	132 x 93.3 x 27.6mm 5.2 x 3.67 x 1.1 Inches	235 x 103 x 27mm 9.25 x 4.06 x 1.1 Inches	440 x 285 x 43mm 17.32 x 11.22 x 1.7 Inches	440 x 285 x 43mm 17.32 x 11.22 x 1.7 Inches