

STTAP Series Seven Line Satellite Trunk Tap

Features:

- Six satellite inputs, 250-2150 MHz
- One Terrestrial input, 5-1000 MHz
- Five values available: 6, 9, 12, 16 or 20 dB
- Two ground lugs
- DC Power passing from output to input
- DC Power blocking on tap ports
- For indoor use only
- Wall mountable



Specifications:

Satellite input ports	6, 250 - 2150 MHz
Terrestrial input ports	1, 5 - 1000 MHz
Impedance	75 Ohms
Operating IF frequency range	250 - 2150 MHz
Flatness in operating frequency range	+/- 0.5 dB
Port to port isolation	>35 dB
Return loss input and output port	12 dB
Return loss tap port	10 dB
Output trunk port to tap isolation loss	20 dB
DC Power passing (output to input only)	1000 mA
Environmental requirements	Indoor or lock box installation
Operational Temperature	-30 to +140°F (-34 to +60 °C)
Dimensions	6.5"W x 4.0"H x 1.5"D

		6 dB Tap	9 dB Tap	12 dB Tap	16 dB Tap	20 dB Tap
Insertion Loss	Input to Output port	4.0 dB	2.5 dB	1.5 dB	1.2 dB	1.0 dB
	Inpt to Tap port	6.0 dB	9.5 dB	12.5 dB	16.5 dB	20.0 dB
	Tap to Input (port 7 only) return path 5-40 MHz	10.5 dB	10.5 dB	13.2 dB	17.2 dB	21.0 dB

Ordering Information:

STTAP06-R0-09	7 Line tap, 6 Satellite, 1 antenna, 6dB
STTAP09-R0-09	7 Line tap, 6 Satellite, 1 antenna, 9dB
STTAP12-R0-09	7 Line tap, 6 Satellite, 1 antenna, 12dB
STTAP16-R0-09	7 Line tap, 6 Satellite, 1 antenna, 16dB
STTAP20-R0-09	7 Line tap, 6 Satellite, 1 antenna, 20dB