

TVI-AC334D-OD4Z

2MP HD-TVI Motorized Lens IR Dome Camera

Features:

- 2MP High Resolution
- Incorporates HD-TVI to provide HD 1080p video over coaxial cable
- Motorized 2.8mm - 12.0mm vari-focal lens
- True Day/Night
- Smart IR
- IR Distance up to 131 Feet
- On Screen Display menu
- IP66 Weather rating
- IK10 Vandal rating
- 12VDC/24VAC Dual voltage powering capability

**HD-TVI High Definition
video over coaxial cable**



Camera

Image sensor	2MP CMOS Image Sensor
Effective Pixels	1928(H) x 1088(V)
Min. Illumination	0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR on
Shutter Time	1/25s to 1/50,000s
Lens	Motorized VF lens; 2.8 - 12 mm @ F1.2
Angle Adjustment	Pan: 0 - 355°, Tilt: 0 - 90°, Rotation: 0-355°
Day & Night	ICR
Synchronization	Internal synchronization
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 turbo HD output
S/N Ratio	More than 62dB

Menu

AGC	Supported
D/N Mode	Color/BW/Smart
White Balance	ATW/MWB
BLC	Supported
Functions	Wide Dynamic Range, Digital noise reduction, Mirror, Smart IR

General

Working Temperature/Humidity	-40 °C – 60 °C (-40 °F – 140 °F)
Humidity	90% or less (non-condensing)
Power Supply	12 VDC / 24 VAC (not included)
Power Consumption	Max. 6.5W
Weather Proof Ratings	IP66
IR Range	Up to 131 Feet
Impact Protection	IK10
Communication	Up the coax
Dimensions	145 x 124.1 mm (5.72" x 4.89")
Weight (approximate)	1600g (3.53 lbs.)



1273ZJ-140B

Wall Mount Bracket

For TVI-AC334D-OD4Z Dome Camera

Ordering Information:

TVI-AC334D-OD4Z 2MP HD-TVI Motorized Lens IR Dome Camera

North American Cable Equipment Inc.

(800) 688-9282 email: sales@northamericancable.com www.northamericancable.com