



*...acoustically designed
for a sound investment*

SD-ODS-GN Weatherproof Outdoor Speaker

Features:

- 5.25" Weatherproof outdoor speaker
- Perfect for gardens, playgrounds and theme parks
- UV Protected
- 360° Horizontal x 40° vertical coverage
- 60 Hz - 20 KHz Frequency response
- 60 Watts RMS power
- Mineral filled polypropylene cone woofer
- Titanium dome tweeter
- 8 Ohm Impedance
- Sold individually

Contents Include:

- 1 SD-ODS-GN Speaker
- 1 Owner's Manual

Description:

The Symphonic Designs satellite series of speakers have been designed with the quality conscious custom home integrator in mind. Designed for indoor and outdoor use, the satellite series speakers are perfect for a wide variety of custom installations. This also makes them a perfect choice of speakers to keep on every installation vehicle as a profitable up-sell item.

The SD-ODS-GN Speakers are manufactured to operate with any quality amplifier designed for use with an 8-ohm impedance load. Because of their well-behaved off-axis response and excellent dispersion your new Symphonic Designs speakers are less critical to position than most loudspeakers. Often simply placing them where they best fit into the decoration scheme is all that is necessary for exceptional performance. The fully sealed design allows these speakers to be fully exposed to outdoor conditions while maintaining reliable delivery of indoor quality sound for years of outdoor listening enjoyment.

Specifications:

Frequency Response:	60 Hz - 20 KHz
RMS Power:	60 watts
Impedance:	8 ohms
Sensitivity (1w/1m):	90 dB
Transformer Tappings:	70V: 32-16-8-4-2W @ 8 ohms 100V: 32-16-8-4W @ 8 ohms
Enclosure Material:	LLDPE (Linear low-density polyethylene)
Environment Rating:	IP56
Woofer:	5.25" (133mm) mineral filled polypropylene cone with rubber suspension, 1"(25mm) ASV coil
Magnet:	10 oz.
Tweeter:	1.2" (30mm) titanium dome
Overall Dimensions:	14.38"W x 16.1"H (365mm x 409mm)



www.symphonicdesigns.net

sales@symphonicdesigns.net

Distributed By: North American Cable Equipment Inc. (800) 688-9282 Fax: (800) 230-1793