

ST-GIP4VFD-MZ

4MP HD Intelligent IR VF Dome Network Camera




Key Features

- High quality image with 4MP, 1/3" CMOS sensor
- 4MP (2688*1520)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296) @ 30/25fps; 2MP (1920*1080) @30/25fps;
- Ultra 265, H.265, H.264, MJPEG
- Intelligent perimeter protection, includes cross line, intrusion, enter area, leave area detection
- Based on target classification, smart intrusion prevention significantly reduces false alarms caused by leaves, birds and lights etc., accurately focuses on humans, motor vehicles and non-motor vehicles
- This cameras technology provides clear image in bright / highly lit areas
- 120dB true WDR technology enables clear image in strong light scene
- Supports 9:16 Corridor Mode
- Built-in Mic
- Alarm:1 in/1 out, Audio: 1 in/1 out
- Smart IR, up to 131 ft (40 m) IR distance
- Supports 256 GB Micro SD card
- IK10 vandal resistant
- IP67 weather rating
- Supports PoE power supply



Dimensions



Available Accessories



Junction Box
ST-GJB04-D



Wall Mount
ST-GWM04-B

ST-GIP4VFD-MZ 4MP HD Intelligent IR VF Dome Network Camera

Camera					
Sensor	1/3", 4.0 megapixel, progressive scan, CMOS				
Lens	2.7 - 13.5mm, AF automatic focusing and motorized zoom lens				
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	2.8 mm	66.4 yds (60.8 m)	26.5 yds (24.3 m)	13.3 yds (12.2 m)	6.6 yds (6.1 m)
	13.5 mm	332.2 yds (303.8 m)	132.8 yds (121.5 m)	66.4 yds (60.8 m)	33.2 yds (30.4 m)
Angle Of View (H)	98.26° - 31.35°				
Angle Of View (V)	54.76° - 18.55°				
Angle Of View (O)	127.74° - 36.99°				
Adjustment Angle	Pan: 0°-360°		Tilt: 0°-90°		Rotate: 0°-360°
Shutter	Auto/Manual, shutter time: 1 - 1/100000s				
Minimum Illumination	Colour: 0.002Lux (F1.2, AGC ON) 0 Lux with IR on				
Day/Night	IR-cut filter with auto switch (ICR)				
S/N	>56dB				
IR Range	Up to 131 ft (40m) IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Defog	Digital Defog				
WDR	120dB				

Video	
Video Compression	Ultra 265, H.265, H.264, MJPEG
H.264 Code Profile	Baseline profile, Main profile, High profile
Frame Rate	Main Stream: 4MP (2688 x 1520), Max 25fps; 4MP (2560 x 1440), Max 25fps; 3MP (2304 x 1296), Max 30fps; 1080P (1920 x 1080), Max 30fps Sub Stream: 720P (1280 x 720), Max 30fps; D1 (720 x 576), Max 30fps; 640 x 360, Max 30fps; 2CIF (704 x 288), Max 30fps; CIF (352 x 288), Max 30fps Third Stream: D1 (720 X 576), Max 30fps; 640 X 360, Max 30fps; 2CIF(704 X 288), Max 30fps; CIF(352 X 288), Max 30fps
Video Bit Rate	128 Kbps-16 Mbps
9:16 Corridor Mode	Supported
OSD	Up to 8 OSDs
Privacy Mask	Up to 4 areas
ROI	Up to 8 areas
Motion Detection	Up to 4 areas

Image	
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital Noise Reduction	2D/3D DNR
Smart IR	Supported
Flip	Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-clockwise
Dewarping	N/A
HLC	Supported
BLC	Supported

Smart	
Smart intrusion Prevention	Cross Line, intrusion, enter area, leave area detection

Event	
Behavior Detection	Motion detection, tampering alarm, audio detection
General Function	Watermark, IP address filtering, alarm input, alarm output, access policy, ARP protection, RTSP authentication, user authentication

Audio	
Audio Compression	G.711
Two-way Audio	Supported
Suppression	Supported
Sampling Rate	8KHZ

Storage	
Edge Storage	Micro SD, up to 256GB
Network Storage	ANR, NAS(NFS)

Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
Client	ST-Station, Guard Station, STVU, Guard Viewer, Star4Live
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
	Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+

ST-GIP4VFD-MZ 4MP HD Intelligent IR VF Dome Network Camera

Interface	
Audio I/O	1 Input: impedance 35kΩ; amplitude 2V [p-p]
	1 Output: impedance 600Ω; amplitude 2V [p-p]
Alarm I/O	1/1
Built-in Mic	Mono Sound
Network	1 RJ45 10M/100M Base-TX Ethernet

Certifications	
Certifications	CE: EN 60950-1, UL: UL60950-1, FCC: FCC Part 15

General	
Power	DC 12V±25%, PoE (IEEE 802.3af)
	Power consumption: Max 7.0W
Dimensions (L × W × H)	Ø5.8" x 4.4"(Φ148 x 111.3 mm)
Net Weight	2.03 lb (0.92kg)
Material	Metal + Plastic
Working Environment	-22 - 140°F (-30 - 60°C), Humidity: ≤95% RH (non-condensing)
Storage Environment	-22 - 140°F (-30 - 60°C), Humidity: ≤95% RH (non-condensing)
Surge Protection	6KV
Ingress Protection	IP67
Vandal Resistant	IK10
Reset Button	Supported
Warranty	2-Year Limited Warranty