

ST-GIP8VFTD-MZ

8MP HD Intelligent IR VF Turret Network Camera





Key Features

- High quality imaging with 8MP, 1/2.8" CMOS sensor
- 8MP (3840 x 2160)@20fps; 5MP (3072 x 1728)@30/25fps; 4MP (2560 x 1440)@30/25fps; 2MP (1920 x 1080) @30/25fps
- Ultra 265, H.265, H.264, MJPEG
- Intelligent perimeter protection, includes cross line, intrusion, enter area, leave area detection
- Based on target classification, smart intrusion prevention significantly reduces false alarms caused by leaves, birds and lights etc., accurately focuses on humans, motor vehicles and non-motor vehicles
- Intelligent face capture
- Intelligent People Flow Counting and Crowd Density Monitoring
- This cameras technology ensures ultra-high image quality in low illumination environment
- 120dB true WDR technology provides clear image in bright, highly lit areas
- Supports 9:16 Corridor Mode
- Built-in Mic
- Smart IR, up to 40m (131ft) IR distance
- Supports 256 GB Micro SD card
- IK10 vandal resistant and IP67 weather rating



Dimensions



Available Accessories



Junction Box
ST-GJB03-E



Wall Mount
ST-GWM03-C

ST-GIP8VFTD-MZ 8MP HD Intelligent IR VF Turret Network Camera

Camera					
Sensor	1/2.8", 8.0 megapixel, progressive scan, CMOS				
Lens	2.8 - 12mm, AF automatic focusing and motorized zoom lens				
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	2.8 mm	95 yds (86.9 m)	26.5 yds (34.8m)	38 yds (17.4m)	9.5 yds (8.7 m)
	12 mm	407.2 yds (372.4 m)	162.9 yds (149 m)	66.4 yds (74.5 m)	40.6 yds (37.2 m)
Angle Of View (H)	107.4° - 29.2°				
Angle Of View (V)	54.2° - 16.3°				
Angle Of View (O)	111.0° - 33.1°				
Adjustment Angle	Pan: 0°-360°		Tilt: 0°-75°		Rotate: 0°-360°
Shutter	Auto/Manual, shutter time: 1 - 1/100000s				
Minimum Illumination	Colour: 0.003Lux (F1.6, AGC ON) 0Lux with IR				
Day/Night	IR-cut filter with auto switch (ICR)				
S/N	>56dB				
IR Range	Up to 131 ft (40m) IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
WDR	120dB				

Video	
Video Compression	Ultra 265, H.265, H.264, MJPEG
H.264 Code Profile	Baseline profile, Main profile, High profile
Frame Rate	Main Stream: 4MP (2688 x 1520), Max 25fps; 4MP (2560 x 1440), Max 25fps; 3MP (2304 x 1296), Max 30fps; 1080P (1920 x 1080), Max 30fps Sub Stream: 720P (1280 x 720), Max 30fps; D1 (720 x 576), Max 30fps; 640 x 360, Max 30fps; 2CIF (704 x 288), Max 30fps; CIF (352 x 288), Max 30fps Third Stream: D1 (720 X 576), Max 30fps; 640 x 360,Max 30fps; 2CIF(704 X 288), Max 30fps; CIF(352 X 288), Max 30fps
Video Bit Rate	128 Kbps-16 Mbps
U-code	Supported
ROI	Up to 8 areas
Video Stream	Triple streams
OSD	Up to 8 OSDs
Privacy Mask	Up to 4 areas

Image	
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Image Setting	Image rotation, brightness, saturation, contrast, sharpness, gain adjustable by web browser
Digital Noise Reduction	2D/3D DNR
Smart IR	Supported
Flip	Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-clockwise
Dewarping	Supported
HLC	Supported
BLC	Supported
Defog	Digital Defog

Smart	
Smart intrusion prevention	Supports false alarm filtering: Line crossing detection, Intrusion detection, Region entrance detection, Region exit detection
Face capture	Supported
Statistical Analysis	Supports People counting, tripwire people counting, and area people counting

Event	
Behavior Detection	Motion detection, tampering alarm, audio detection
General Function	Watermark, IP address filtering, alarm input, alarm output, access policy, ARP protection, RTSP authentication, user authentication

Audio	
Audio Compression	G.711
Audio Bitrate	64 Kbps
Suppression	Supported
Sampling Rate	8KHZ

Storage	
Edge Storage	Micro SD, up to 256GB
Network Storage	ANR, NAS(NFS)

Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP,SSL/TLS, SSH
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API,SDK
Client	ST-Station, Guard Station, STVU, Guard Viewer, Star4Live
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
	Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+

ST-GIP8VFTD-MZ 8MP HD Intelligent IR VF Turret Network Camera

Interface	
Audio I/O	N/A
Alarm I/O	N/A
RS485	N/A
Built-in Mic	Mono Sound
Built-in Speaker	N/A
WIFI	N/A
Network	1 RJ45 10M/100M Base-TX Ethernet
Video Output	N/A

Certifications	
EMC	FCC CFR 47 Part 15, EN 55032:2015 EN 55024:2010, EN 61000-3-2:2014 EN 61000-3-3-2013
Safety	IEC 62368-1, EN 62368-1, UL 62368-1
Environment	CE-ROHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU); REACH (Regulation (EC) No 1907/2006)
Protection	Ingression protection: IP67 (IEC 60529-2013) Vandal resistant: IK10 (IEC 62262:2002)

General	
Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 9.0W
Power Interface	Ø 5.5mm coaxial power plug
Dimensions (L × W × H)	Ø5.1" x 4.3" (Φ129 x 110 mm)
Net Weight	1.52 lb (0.69kg)
Material	Metal
Working Environment	-22 - 140°F (-30 - 60°C), Humidity: ≤95% RH (non-condensing)
Storage Environment	-22 - 140°F (-30 - 60°C), Humidity: ≤95% RH (non-condensing)
Surge Protection	6KV
Ingress Protection	IP67
Vandal Resistant	IK10
Reset Button	Supported
Warranty	2-Year Limited Warranty