

2MP HD-TVI Fixed Lens IR Bullet Camera



HD-TVI High Definition video over coaxial cable

Features:

- 2MP High Resolution
- Incorporates HD-TVI to provide HD 1080p video over coaxial cable
- 2.8mm or 3.6mm lens available
- True Day/Night
- Smart IR
- Wide Dynamic Range
- IR Distance up to 131 Feet
- On Screen Display menu
- IP67 Weather rating



Camera

Image sensor	2MP CMOS Image Sensor
Effective Pixels	1920(H) x 1080(V)
Min. Illumination	Color: 0.005 Lux @ (F2.0,AGC ON),0 Lux with IR on
Shutter Time	PAL: 1/25s to 1/50,000s NTSC: 1/30s to 1/50,000s
Lens	2.8mm or 3.6mm Fixed
Horizontal Field of View	2.8mm lens: 103.5° 3.6mm lens: 82.6°
Lens Mount	M12
Angle Adjustment	Pan: 0 - 360°, Tilt: 0 - 180°, Rotation: 0-360°
Day & Night	ICR
Synchronization	Internal synchronization
WDR	120dB
Video Frame Rate	1080p@25fps / 1080p@30fps
HD Video Output	1 turbo HD output
S/N Ratio	More than 62dB



Menu

AGC	Supported
D/N Mode	Smart IR / Color / BW
White Balance	Auto / Manual
BLC	WDR / BLC / HLC / OFF
3D DNR (Digital Noise Reduction)	On
Language	English
Functions	Brightness, sharpness, mirror, Smart IR

General

Working Temperature/Humidity	-40 °C – 60 °C (-40 °F – 140 °F)
Humidity	90% or less (non-condensing)
Power Supply	12 VDC (not included)
Power Consumption	Max. 4W
Weather Proof Ratings	IP67
IR Range	Up to 131 Feet
Communication	Up the coax
Dimensions	86.7 x 81.6 x 226mm (3.41" x 3.23" x 8.67")
Weight (approximate)	680g (1.5 lbs.)

Ordering Information:

ST-HDC2FB-EXIR	2MP HD-TVI 3.6mm Fixed Lens IR Bullet Camera
ST-HDC2FB-EXIR-2.8	2MP HD-TVI 2.8mm Fixed Lens IR Bullet Camera



ST-JBMB
Junction box for
ST-ST-HDC2FB-EXIR
Series