

2MP IP Fixed Lens Dome Camera



Features:

- 2MP High Resolution
- HD real-time video
- 3D DNR & DWDR & BLC
- IR Distance up to 98 Feet
- IP66 Weather rating
- PoE Compatible
- IK10 Vandal rating



Camera

Image sensor	1/3" Progressive Scan CMOS
Min. illumination	0.07Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Speed	1/3 s to 1/100,000 s
Lens Options	2.8mm@ F2.0, Angle of view: 98.5° 4.0mm@ F2.0, Angle of view: 79°
Lens mount	M12
Angle adjustment	Pan: 0 to 360 degrees, tilt: 0 to 65 degrees
Day & Night	IR cut filter with auto switch
Digital noise reduction	3D DNR
Wide Dynamic Range	Digital WDR
Video compression	H.264 / MJPEG
Video Bit Rate	32 Kbps – 16 Mbps
Dual stream	Yes



Image

Max. Image Resolution	1920 × 1080
Frame rate	50Hz: 25fps(1920 × 1080), 25fps (1280 × 960), 25fps (1280 × 720) 60Hz: 30fps(1920 × 1080), 30fps (1280 × 960), 30fps (1280 × 720)
Image settings	Rotate mode, Saturation, Brightness, Contrast adjustable by client software or web browser
Backlight compensation	Yes, zone configurable
ROI	Supported



Network

Network storage	Local storage - built in micro SD/SDHC/SDXC card slot up to 64GB; NAS
Alarm trigger	Intrusion detection, motion detection, dynamic analysis, Tampering alarm, network disconnect, IP address conflict, storage full, storage error
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
General function	Flickerless, dual stream, heartbeat, mirror, password protection, watermark
Security	User Authentication, watermark
Standard	ONVIF, PSIA, CGI
Client	Central management software

Interface

Communication Interface	1 RJ45 10M/100M Ethernet interface
-------------------------	------------------------------------

General

Operating conditions	-30 °C – 60 °C (-22 °F – 140 °F)
Humidity	95% or less (non-condensing)
Power supply	12 VDC ± 10% , PoE (802.3af) (not included)
Power consumption	5W MAX (Max. 7 W as IR cut filter on)
Ingress Protection level	IP66
IR Range	Up to 98 Feet
Impact protection	IK10
Dimensions	4.4" × 3.96"
Weight	500g (1.1 lbs)



ST-WM1
Wall mount for
ST-IP2FD

ST-JB1
Junction box for
ST-IP2FD

Ordering Information:

ST-IP2FD	2MP IP 4mm Fixed Lens Dome Camera with IR
ST-IP2FD-2.8	2MP IP 2.8mm Fixed Lens Dome Camera with IR