


ST-IP4FB-LS-2.8 | ST-IP4FB-LS-4 | ST-IP4FB-LS-6

4MP IP Fixed Lens Bullet Camera

Looking for high quality HD IP video surveillance cameras but do not want to pay the high prices? SecurityTronix Lite Series has your solution. The Lite Series 4 Mega Pixel High Resolution, IP fixed lens camera transmits and receives video and controls data over a single network cable. This compact mini bullet camera packs a big punch and is suited for any commercial application. The free STGO2 app allows users to view their cameras on their mobile devices anytime with ease. Cameras are Plug n Play when paired with SecurityTronix Network Video Recorders (NVR) that have built in PoE. Need to make sure you are not going to lose recorded data... The Lite Series cameras connect to SecurityTronix ST LIVE cloud based platform for retention of recorded video off site. The robust design includes an IP67 weather rating, Digital Wide Dynamic Range (DWDR) to provide a clear image when a lighting change occurs behind the subject being viewed, and IR LEDs allow the camera to see in total darkness up to 98 feet. The camera can be powered via PoE (power over Ethernet) or locally with a 12V DC power supply. Power supply not included.



Dimensions



Key Features

- 1/3" progressive scan CMOS
- 2560 × 1440@20fps
- 2.8, 4 and 6 mm fixed lens
- H.265+, H.265, H.264+, H.264
- Dual stream
- Digital WDR (Wide Dynamic Range)
- 3D DNR (Digital Noise Reduction)
- Up to 98' IR range
- PoE (Power over Ethernet)
- IP67

Available Accessories



Junction Box Camera Mount
ST-JBMB

STGO2
FREE APP
View from your phone
or mobile device
anytime, anywhere!
STGO2
Available on the App Store | GET IT ON Google Play

ST-IP4FB-LS-2.8 | ST-IP4FB-LS-4 | ST-IP4FB-LS-6 4MP IP Fixed Lens Bullet Camera

Camera

Image Sensor	1/3" progressive scan CMOS
Min. Illumination	Color: 0.01 Lux @(F1.2, AGC ON), 0.028Lux @ (F2.0, AGC ON)
Shutter Speed	1/3 s to 1/100, 000 s
Slow Shutter	Yes
Auto-Iris	No
Day & Night	IR cut filter
Digital Noise Reduction	3D DNR
WDR	Digital WDR (Wide Dynamic Range)
Angle Adjustment (Bracket)	Pan: 0° to 360°, tilt: 0° to 180°, rotation: 0° to 360°

Lens

Focal Length	2.8, 4 and 6 mm
Aperture	F2.0
Focus	No
FOV	2.8 mm, horizontal FOV 100°, vertical FOV 55°, diagonal FOV 117° 4 mm, horizontal FOV 77°, vertical FOV 42°, diagonal FOV 88° 6 mm, horizontal FOV 51°, vertical FOV 28°, diagonal FOV 58°
Lens Mount	M12

IR

IR Range	Up to 98'
Wavelength	850nm

Compression Standard

Video Compression	Main stream: H.265/H.264 Sub stream: H.265/H.264/MJPEG
H.264 Type	Baseline Profile/Main Profile/High Profile
H.264+	Main stream supports
H.265 Type	Main Profile
H.265+	Main stream supports
Video Bit Rate	32 Kbps to 8 Mbps

Image

Max. Resolution	2560 × 1440
Main Stream Max. Frame Rate	50Hz: 20fps (2560 × 1440), 25fps (2304 × 1296, 1920 × 1080, 1280 × 720) 60Hz: 20fps (2560 × 1440), 30fps (2304 × 1296, 1920 × 1080, 1280 × 720)
Sub-stream Max. Frame Rate	50Hz: 25fps (640 × 480, 640 × 360, 320 × 240) 60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)
Image Enhancement	BLC, 3D DNR
Image Setting	Saturation, brightness, contrast, sharpness, AGC, white balance adjustable by client software or web browser
Day/Night Switch	Auto, scheduled

Smart Features

Region of Interest	1 fixed region for main stream and sub-stream
--------------------	---

Network

Network Storage	NAS (NFS, SMB/CIFS)
Alarm Trigger	Motion detection, video tampering alarm, illegal login
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour
General Function	Anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark, IP address filter
Firmware Version	5.5.3
API	ONVIF (PROFILE S, PROFILE G), ISAPI
Simultaneous Live View	Up to 6 channels
User/Host	Up to 32 users 3 levels: Administrator, Operator and User
Client	STGO2, Guarding Vision Client
Web Browser	IE8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+

Interface

Communication Interface	1 RJ45 10M/100M self-adaptive Ethernet port
-------------------------	---

General

Operating Conditions	-22 °F to 122 °F (-30 °C to 50 °C), humidity: 95% or less (non-condensing)
Power Supply	12 VDC ± 25%, 5.5 mm coaxial power plug PoE (802.3af, class 3)
Power Consumption and Current	12 VDC, 0.4 A, Max: 5 W PoE: (802.3af, 36 V to 57 V), 0.2 A to 0.13 A, Max: 7 W
Protection Level	IP67 TVS 2000V lightning protection, surge protection and voltage transient protection
Material	Metal & Plastic
Dimensions	Camera: 2.7" × 6.8" (Ø 70 × 172.7mm) With package: 8.5" × 4.8" × 4.6" (216 × 121 × 118 mm)
Weight	Camera: Approx. 0.62 lb. (280 g) With package: Approx. 1.17 lb. (530 g)
Warranty	2-Year Limited Fixed Camera Warranty